-----

REVISION DATE: 06-17-2011 SUPERSEDES: None

## SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### COMPANY INFORMATION

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street

Aurora, IL 60504

06-17-2011

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT NUMBER: ACCUCOLOR EFX 999 GOLD

PRODUCT DESCRIPTION: Epoxy resin PRODUCT IDENTIFIER: 829470PM

### **SECTION 2: HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW** 

PHYSICAL STATE: Liquid COLOR: White

ODOR: Mild Aromatic

Moderate eye irritant.

Causes skin irritation. May cause allergic skin reaction.

Harmful if swallowed.

Cancer hazard.

### POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

SKIN: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. May cause sensitization.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Overexposure to crystalline silica may cause silicosis.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. Harmful if swallowed. Irritating to mouth, throat, and stomach.

LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Skin Lungs

#### REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica

Titanium dioxide

Carbon black

Titanium dioxide (Rutile)

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Skin disease including eczema and sensitization; Lung disease

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT
Epoxy resin	25068-38-6	50 - 70
Epoxy resin	68609-97-2	10 - 30
Crystalline silica	14808-60-7	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Wax, polyethylene	9002-88-4	0.1 - 1
Carbon black	1333-86-4	0.1 - 1
Titanium dioxide (Rutile)	1317-80-2	0.1 - 1

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

## **SECTION 4: FIRST AID MEASURES**

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

#### **SECTION 5: FIRE FIGHTING MEASURES**

FLASH POINT:

AUTOIGNITION TEMPERATURE:

LOWER EXPLOSIVE LIMIT (% in air):

UPPER EXPLOSIVE LIMIT (% in air):

Not applicable
Not established
Not established

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material will burn in a fire.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

# SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this

MSDS. Additional precautions may be necessary based on special

circumstances created by the spill including; the material spilled, the quantity

of the spill, the area in which the spill occurred.

CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers

for disposal. Keep spilled product out of sewers, watersheds, or water

systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

## **SECTION 7: HANDLING AND STORAGE**

Handling: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in

a well ventilated area.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter if product is sprayed. Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

### **EXPOSURE LIMITS:**

Chemical Name	ACGIH EXPOSURE LIMITS	OSHA PEL	
Epoxy resin	Not established	Not established	
Epoxy resin	Not established	Not established	
Crystalline silica	0.025 mg/m3 TWA (respirable fraction)	((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust))	
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA (total dust)	
Wax, polyethylene	2 mg/m3 TWA (fume)	Not established	
Carbon black	3.5 mg/m3 TWA	3.5 mg/m3 TWA	
Titanium dioxide (Rutile)	Not established	15 mg/m3 TWA (total dust)	

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE: Liquid COLOR: White

ODOR: Mild Aromatic ODOR THRESHOLD: Not established

WEIGHT PER GALLON (lbs.): 8.7

1.08 SPECIFIC GRAVITY:

SOLIDS (% by weight): 100.0

Not established pH: FLASH POINT: Not applicable BOILING POINT (deg. C): Not established FREEZING/MELTING POINT (deg. C): Not established VAPOR PRESSURE (mm Hg): Not established VAPOR DENSITY: Not established **EVAPORATION RATE:** Not established OCTANOL/WATER COEFFICIENT: Not established VOC, weight percent Not determined

### **SECTION 10: STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

## **SECTION 11: TOXICOLOGICAL INFORMATION**

COMPONENT	LD50/LC50	
Epoxy resin	Oral LD50 Rat = $11.4 \text{ g/kg}$	
	Dermal LD50 Rabbit > 20 ml/kg	
Epoxy resin	Not established	
Crystalline silica	Not established	
Titanium dioxide	Not established	
Wax, polyethylene	Inhalation LC50 Mouse = 12000 mg/cu m/4H	
Carbon black	Oral LD50 Rat > 15400 mg/kg Dermal LD50 Rabbit > 3 g/kg	
Titanium dioxide (Rutile)	Not established	

TOXICOLOGY SUMMARY: No additional health information available.

### **SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available

# **SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended. Consult state, local or provincial authorities for more restrictive requirements.

## SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: **NOT REGULATED** IATA: NOT REGULATED

\_\_\_\_\_

### **SECTION 15: REGULATORY INFORMATION**

**INVENTORY STATUS** 

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from

DSL requirements.

EUROPEAN EINECS: As a result of the introduction of REACH into Europe, this product cannot be

imported into Europe unless the REACH requirements are met.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

#### FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name CAS# %

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2B D2A

## STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Quartz (Carcinogen)	14808-60-7	1 - 5
Carbon black (Carcinogen)	1333-86-4	0.1 - 1
Nickel compounds (Carcinogen)	12607-70-4	0.001 - 0.01
Benzene, ethyl- (Carcinogen)	100-41-4	0.001 - 0.01
Phenyl glycidyl ether (Carcinogen)	122-60-1	< 10 ppm
Epichlorohydrin (Carcinogen)	106-89-8	< 10 ppm
Lead compounds (Carcinogen)		< 10 ppm
Cadmium compounds (Carcinogen)		< 10 ppm
Benzene (Carcinogen)	71-43-2	< 10 ppm
Benzene (Developmental toxin)	71-43-2	< 10 ppm
(Phenoxymethyl) oxirane (Male reproductive toxin)	122-60-1	< 10 ppm
Epichlorohydrin (Male reproductive toxin)	106-89-8	< 10 ppm
Benzene (Male reproductive toxin)	71-43-2	< 10 ppm

### **SECTION 16: ADDITIONAL INFORMATION**

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 1 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.