



1. PRODUCT NAME

TEC® 714 and 714W
Premium Cove Base Adhesive
(TA-714)



2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800.952.2368 Fax
tecspecialty.com

3. DESCRIPTION

TEC® 714 Premium Cove Base Adhesive is designed for easy installation of vinyl, rubber and TPR cove base.

Key Features and Benefits

- Ideal for rubber/vinyl/TPR
- Easy to apply
- Strong bond
- Easy water clean-up
- Excellent wet-suction
- Low odor
- Low VOC

Packaging

TEC® 714:

29 fl. oz. cartridges (857 mL)
2 gallon plastic pails (7.58 L)

Product #3300156211
Product #3300151011

TEC® 714W:

29 fl. oz. cartridges (857 mL)

Product #7047436211

Coverage

Coverage will vary with the application method and cove base width. Figures below are presented only as guidelines.

Application Method	Approximate Coverage for 4" (10.16 cm) cove base
½" (3 mm) V-notch trowel	240-300 lineal feet (73-91 lineal meters) per gallon (3.78 L)
Extrusion application using a 2, 3 or 5-hole applicator nozzle	30-70 lineal feet (9-21 lineal meters) per 29 fl. oz (857 mL) cartridge

Suitable Interior Substrates

When properly prepared, suitable substrates include:

- Cured plaster
- Cured concrete
- Gypsum drywall
- Plywood
- Masonry

Substrate Preparation

Apply over clean, dry, structurally sound wall surfaces. Paint or varnish must be removed by sanding. Do not use over non-porous surfaces.

Storage

Store in cool, dry location. Do not store open containers.

Shelf Life

Maximum of 1 year from date of manufacture in unopened container.

Limitations

- Do not apply over wallpaper or water soluble surfaces.
- Do not apply over non-porous surfaces such as vinyl wall coverings or plastic laminates.
- Do not use when temperature is below 50°F (10°C).
- Freeze/thaw stable to 10°F (-12°C) for a minimum of 5 cycles.
- If product freezes, slowly bring to room temperature.

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC® brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Physical Properties

TEC® 714 and TEC® 714W Premium Cove Base Adhesive (TA-714/714W)	
Description	
Base	Acrylic latex
Physical State	Smooth, medium paste
Color	Tan and white
Open Time	15 to 20 minutes
VOC/Liter of Material	TEC® 714: 10 g/L, less water TEC® 714W: 5 g/L, less water
Freeze/Thaw Stability	Freeze/thaw stable to 10°F (-12°C) for a minimum of 5 cycles. If frozen, slowly bring material back to room temperature and stir before using.
Storage	Store in cool, dry location. Do not store open containers.
Shelf Life	Maximum 1 year from date of manufacture in properly stored, unopened package.

5. INSTALLATION INSTRUCTIONS

Application

Rolled or warped cove base should be laid flat for 24 hours and allowed to return to normal state before adhesive application. Cove base backing should be free of surface contaminants prior to installation. For best results, cove base, room and adhesive should be kept at a minimum of 60°F (16°C) for 48 hours before and after installation. For ease of installation, apply an even layer of adhesive to the back of the cove base. If extrusion application is desired, cut spout, puncture inner seal and insert cartridge into applicator. Use cove base nozzle attachment with two holes for 2½" (6.4 cm) base, 3 holes for 4" (10.16 cm) base and 5 holes for 6" (15.24 cm) base. Apply adhesive to the back of the cove base. Press cove base firmly into place using a hand roller to insure adhesive transfer within 20 minutes after application. Installation of cove base over irregular or curved surfaces may require bracing of cove base until adhesive has set.

Clean-up

Clean wet adhesive from cove base and surrounding materials with a wet cloth immediately after installation. Dried adhesive can be removed by mechanical means only.

6. AVAILABILITY

TEC® Premium Tile and Stone Installation Products are available nationwide.
To locate TEC® products in your area, please contact:
Phone: 800-832-9002
Website: tecspecialty.com

7. WARRANTY

For warranty details, see your sales associate or tecspecialty.com.

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical assistance

Information is available by calling the Technical Support Hotline.
Toll Free: 800-832-9023
Fax: 630-952-1235

Technical and safety literature

To acquire technical and safety literature, please visit our website at tecspecialty.com.

10. FILING SYSTEM

Division 9

tecspecialty.com