

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Fiberglass-reinforced luxury resilient sheet vinyl that can be heat welded. Suitable for Residential and Light Commercial environments.

1.2 **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
 30000 Aurora Rd. (440) 543-8916
 Solon, Ohio 44139
 Web: www.tarketthome.com

1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Luxury resilient sheet vinyl made from ortho-phthalate free, virgin raw materials.

1.3.2 **Characteristics:**

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** 60000
- **Overall Thickness:** 0.080" (2.03 mm)
- **Wearlayer Thickness:** 0.020" (0.51 mm)
- **Width:** 12' (3.6 m)
- **Maximum Roll Size:** 100 yd² (83.6 m²)
- **Weight per Square Yard:** 4.81 lbs. (2.18 kg)

2. PRODUCT DETAILS AND TECHNICAL DATA

2.1 **Sheet Material:** ASTM F1303 Type 1, Grade 1, Class C

2.2 **Slip Resistance:** ASTM D2047 >0.5

2.3 **Flexibility:** ASTM F137 Passes

2.4 **Static Load Limit:** ASTM F970 175 lbs./in² (12.3 kg/cm²)

2.5 **Heat Stability:** ASTM F1514 ΔE<8

2.6 **Light Stability:** ASTM F1515 ΔE<8

2.7 **Sound Reduction:** ASTM E2179 ΔIIC 13 dB

2.8 **Stain Resistance:** ASTM F925 Passes

2.9 **Fire Performance:** ASTM E648 >0.45 W/cm²

2.10 **Smoke Density:** ASTM E662 <450

2.11 **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness

2.12 **FloorScore® Certification:** SCS-FS-02746

2.13 **Asthma and Allergy Certified:** AAFC: 1155/11/05/01/2066

3. INSTALLATION

See FiberFloor installation instructions found at www.tarketthome.com for complete details.

3.1 **Methods:**

- Releasable
- Permanent
- Floating Glueless

3.2 **Adhesive:**

- **Tarkett Qbond One**
Releasable - Medium Nap Roller
Permanent - 1/32" x 1/16" x 1/32" trowel

3.3 **Seaming:**

- **Seam Sealer:** Tarkett DT-65 (Low Gloss)
- **Heat Welding**

4. AVAILABILITY AND COST

Available through Tarkett Distributors and Retailers.

5. MAINTENANCE

See Residential Maintenance instructions found at www.tarketthome.com for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarketthome.com

Contact Technical Support at (888) 639 8275, or E-mail Resilient.TechnicalSupport@tarkett.com

7. WARRANTY

- LIFETIME LIMITED RESIDENTIAL WARRANTY
 Aquaguard® 2 year "No Questions Asked" Warranty
- 15 YEAR LIGHT COMMERCIAL WARRANTY



**ORTHO-PHTHALATE
FREE**

Tarkett North America

Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 888-639-8275

Resilient.TechnicalSupport@tarkett.com

www.tarketthome.com

